

DIRECT DRIVE AIR COMPRESSOR



- **Intelligent Microcomputer Control System:** Provides advanced automation and precise control for efficient compressor operation.
- **Large, Low-Speed Air-End:** Ensures optimized performance with enhanced durability and efficiency.
- **Low Vibration and Noise:** Operates quietly with minimal vibration, eliminating the need for a foundation and allowing easy mobility.
- **User-Friendly Operation:** Designed for automatic operation, requiring minimal supervision or manual intervention.



MODEL: HD10

ITEM	TECHNICAL PARAMETERS		
	HD10	HD10	HD10
MODEL	HD10	HD10	HD10
POWER	7.5KW (10HP)		
F.A.D	38 CFM	31 CFM	28 CFM
MEDIUM	AIR		
RATED PRESSURE	116 PSI	145 PSI	181 PSI
COOLING METHOD	AIR-COOLED		
TRANSMISSION METHOD	DIRECT DRIVE		
AIR DISCHARGE TEMPERATURE	AMBIENT TEMPERATURE +59°F		
CONTROL MODE	MICROCOMPUTER CONTROL SYSTEM		
START MODE	DIRECT START		
AIR INLET TEMPERATURE	~114°F		
AMBIENT TEMPERATURE	23-113°F		
AIR INLET PRESSURE	14.7 PSI		
MOTOR ROTATION SPEED	3540 R/MIN		
MOTOR PROTECTION LEVEL	IP55		
MOTOR INSULATION LEVEL	F LEVEL		
MOTOR SERVICE FACTOR	1.2		
POWER SUPPLY	230/460V-60HZ-3PH		
MAXIMUM RELATIVE HUMIDITY	0.95		
AIR OUTLET CONNECTION	1/2"		
DIMENSION	36x27x35		
NET WEIGHT	430 LBS		
NOISE LEVEL	68±2dB (A)		