

DIRECT DRIVE

AIR COMPRESSOR



- **Intelligent Microcomputer Control System:**
Provides advanced automation and precise control for efficient compressor operation.
- **Large, Low-Speed Air-End:** Ensures optimized performance with enhanced durability and efficiency.
- **Low Vibration and Noise:** Operates quietly with minimal vibration, eliminating the need for a foundation and allowing easy mobility.
- **User-Friendly Operation:** Designed for automatic operation, requiring minimal supervision or manual intervention.



MODEL: HD25

ITEM	TECHNICAL PARAMETERS		
	HD25	HD25	HD25
MODEL	HD25	HD25	HD25
POWER	18.5 KW (25HP)		
F.A.D	106 CFM	77 CFM	70 CFM
MEDIUM	AIR		
RATED PRESSURE	116 PSI	145 PSI	181 PSI
COOLING METHOD	AIR-COOLED		
TRANSMISSION METHOD	DIRECT DRIVE		
AIR DISCHARGE TEMPERATURE	AMBIENT TEMPERATURE +59°F		
CONTROL MODE	MICROCOMPUTER CONTROL SYSTEM		
START MODE	Y-△ START		
AIR INLET TEMPERATURE	~114°F		
AMBIENT TEMPERATURE	23-113°F		
AIR INLET PRESSURE	14.7 PSI		
MOTOR ROTATION SPEED	3540 R/MIN		
MOTOR PROTECTION LEVEL	IP55		
MOTOR INSULATION LEVEL	F LEVEL		
MOTOR SERVICE FACTOR	1.2		
POWER SUPPLY	230/460V-60HZ-3PH		
MAXIMUM RELATIVE HUMIDITY	0.95		
AIR OUTLET CONNECTION	1"		
DIMENSION	55x34x46		
NET WEIGHT	926 LBS		
NOISE LEVEL	68±2dB (A)		